

eXtreme® Cat 6A LSZH Patch Cords

APPLICATION

Leviton eXtreme Cat 6A LSZH Patch Cords exceed all channel and component performance requirements in ANSI/TIA-568-C.2 and ISO 11801 Class E_A from 1 MHz to 500 MHz to support 10GBASE-T applications (IEEE 802.3an). eXtreme Cat 6A patch cords are backwards compatible to support 100BASE-T and 1000BASE-T, and provide a seamless network migration path to 10 Gigabit Ethernet and other high-bandwidth applications.



SPECIFICATION

Cat 6A LSZH patch cords shall meet or exceed the requirements for Cat 6A channel and component performance described in ANSI/TIA-568-C.2 and ISO 11801. Patch cords shall be a stranded conductor with a standard 8-position modular plug on each end. The cords shall be available in standard lengths of 1, 2, 3, and 5 meters. The manufacturer shall provide a one-year limited product warranty. The manufacturer shall also provide an extended warranty against defects in material and workmanship, and an application guarantee when installed as part of a certified system.

FEATURES

- F/UTP stranded construction provides exceptional alien crosstalk (AXT) suppression in a Cat 6A channel
- Stranded conductors ensure extended life and long-term channel integrity
- Color-matched cords and boots
- Available in three different ANSI/TIA 606-B compatible colors
- Available in four standard lengths (custom lengths available)

DESIGN CONSIDERATIONS

- ANSI/TIA channel performance limits total length of patching and equipment cords to 32 feet (10 meters) per ANSI/TIA-568-C.2
- Use where low-smoke zero-halogen materials are required
- Available in four standard lengths

STANDARDS COMPLIANCE

- ANSI/TIA-568-C.1
- ANSI/TIA-568-C.2 Cat 6A
- ISO 11801 Class E_A
- ANSI/TIA-568-C.0
- IEEE 802.3an 10GBASE-T
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3u 100BASE-T
- IEEE 802.3af Power over Ethernet (PoE)
- IEEE 802.3at Power over Ethernet (PoE+)
- ANSI/TIA-1096-A (formerly FCC Part 68)
- EN 50173
- IEC 60332-1
- IEC 60134-2
- IEC 60754-1
- IEC 60754-2

PHYSICAL SPECIFICATIONS

- Available Lengths: See page two
- Outer Diameter (O.D.): 0.25" (6.35mm)
- Materials: 26-gauge, F/UTP stranded conductor, modular non-keyed 8P8C, 94V-0 rated
- Color: White, blue, grey (color-matched strain-relief boots)

COUNTRY OF ORIGIN


Taiwan

WARRANTY INFORMATION

For a copy of Leviton product warranties, visit www.leviton.com/warranty.

ELECTRONIC FILES

For CAD files, typical specs, or technical drawings (.DXF, .DWG), visit www.leviton.com.



6AZ10-xxx

PART NUMBERS

Description	Part No.
eXtreme® Cat 6A LSZH Patch Cord, F/UTP stranded, 1-meter length	6AZ10-xx1
eXtreme Cat 6A LSZH Patch Cord, F/UTP stranded, 2-meter length	6AZ10-xx2
eXtreme Cat 6A LSZH Patch Cord, F/UTP stranded, 3-meter length	6AZ10-xx3
eXtreme Cat 6A LSZH Patch Cord, F/UTP stranded, 5-meter length	6AZ10-xx5

xx = Colors: (BL) blue, (WH) white, (GY) grey



Leviton Network Solutions
2222 - 222nd St. SE
Bothell, WA 98021-4416

Asia / Pacific
T +1.631.812.6228
E infoasean@leviton.com

Canada
T +1.514.954.1840
E pcservice@leviton.com

Caribbean
T +1.954.593.1896
E infocaribbean@leviton.com

China
T +852.2774.9876
E infochina@leviton.com

Colombia
T +57.1.743.6045
E infocolombia@leviton.com

tel 1-800-824-3005
tel +1-425-486-2222
appeng@leviton.com
www.leviton.com

Europe
T +33.6.8869.1380
E infoeurope@leviton.com

India / SAARC
T +971.4.886.4722
E infoindia@leviton.com

Mexico
T +52.55.5082.1040
E lsamarketing@leviton.com

Middle East & Africa
T +971.4.886.4722
E lmeinfo@leviton.com

South Korea
T +82.2.3273.9963
E infokorea@leviton.com